Specifications

Load Capacity 2200 lbs. 49" Fork Length 21.5"/27 **Overall Fork Widths Lowered Fork Height** 3.3" **Raised Fork Height** 31.5" 6.3" Fork Width Weight 400 lbs. Casters 7" x 2" 3" x 2" **Load Rollers** Load Center 24.5" 65" **Overall Length** 48.25" **Turning Radius Battery** 12V / 100Ah 12V / 10A Charger

The CJ22XB Battery Hi-Rise Scissor Lift features manual push – battery lift operation and is designed to handle applications such as lifting and transporting skids and bottomless containers, loading and unloading conveyor systems, and is also perfectly suited as a mobile work station.

Built to work like a Stacker and a Pallet Truck combined, the ergonomic design of the CJ22XB enables the operator to place the load at the required work height thereby eliminating bending and back injuries which results in reduced costly workman compensation claims.

Standard Features

Frame

 Rugged Heavy Duty Frame constructed of one-piece formed channel steel offering light weight strength.

Forks

 Reinforced for added strength with tapered ends for easy pallet entry.

Paint

• The CJ22XB boasts a quality Powder Coat finish.

Hydraulic Pump

- Quality design complete with a special lowering valve allowing controlled rate of descent, and an overload bypass valve.
- The two stage piston rode design ensures stability in the raised position.

Scissor Legs

 The extra long steel scissor legs provide extra stability particularly when handling unevenly loaded skids.

Pump Stroke

 Features a full 90 degree top to bottom stroke requires only 18 strokes to raise the forks to the maximum lift

Handle

• Featuring a reinforced base, the spring-a-matic handle returns to the upright position automatically.

Control Handle

 The control handle has three positions (raise/neutral/ lower) fingertip control. Ergonomically designed and free of pinch points.

Steering

 Featuring 150 degree pivot action for greater maneuverability with 7" polyurethane swivel casters providing maximum rolling ease and maneuverability in tight areas.

Load Rollers

• The durable 3" polyurethane rollers are situated in the scissor legs for easy mobility.

Brakes

 The self adjusting stabalizers are automatically applied when lifting loads higher than 15.75" which ensures that the load will remain stable particularly when using the truck as a work positioner.

Charger

 Features an external 12 volt charger that plugs into any standard 110 volt outlet.

Battery Lift Operation

 Raises the truck (empty) to the maximum height in approx. 15 seconds.