

HWX PWX



ELECTRIC 24 VOLT
WALKIE/RIDER LOW LIFT PALLET TRUCK
6000 / 8000 lbs.
(2720 / 3630 kg)

STANDARD SPECIFICATIONS

30/40

Manufacturer's Designation		HWX 30	HWX 40	PWX 30	PWX 40
Load Capacity	lbs(kg)	6000 (2720)	8000 (3630)	6000 (2720)	8000 (3630)
Height	in(mm)	46.7 (1187)	46.7 (1187)	32.39 (823)	32.39 (823)
Width	in(mm)	36.0/32.0 (914/813)	36.0/32.0 (914/813)	36.0/32.0 (914/813)	36.0/32.0 (914/813)
Length to fork face (For small/large battery comp.)	in(mm)	35.8/41.8 (655/1062)	35.8/41.8 (655/1062)	28.27/34.27 (718/870)	28.27/34.27 (718/870)
Outside Turning Radius (For small/large battery comp.)	in(mm)	76.2/82.2 (1936/2088)	76.2/82.2 (1936/2088)	69.1/75.1 (1755/1908)	69.1/75.1 (1755/1908)
Travel speed loaded / unloaded	mph (kph)	6.4/8.4 (10.4/13.5)	6.1/8.4 (9.8/13.5)	3.3/4.0 (5.3/6.4)	3.1/4.0 4.9/6.4)
Power Unit		24 volt	24 volt	24 volt	24 volt

STANDARD FEATURES

- Enclosed AC traction motor and control • Electromagnetic brake • 48" x 27" Forks • AC control • 24 Volt • Heavy-duty undercarriage • Two forms of regenerative braking • Entry/exit rollers • Diagnostic dash display • Hour meter • Battery discharge indicator with interrupt • Selector for high or low travel speed range



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.